

Caratteristiche tecniche

Telecamera di videosorveglianza mobile con OCR, e-Killer scan

- 1/1.8" Progressive Scan CMOS
- Full HD1080p video
- Up to 60fps frame rate
- Ultra-low light
- Slow shutter
- 120dB WDR
- 3D DNR
- Up to 50m IR range
- Motorized lens with Smart Focus
- S: audio/alarm IO
- Support 128G on-board storage
- DC12V/PoE
- IP67
- Batterie 2 X 12A

Reti

LTE:

- LTE FDD: B1/B3/B5/B7/B8/B20
- LTE TDD: B38/B40/B41
- LTE CAT4 up to 70 Mbps DL
- Class 3 (23dBm \pm 2dB) for LTE FDD
- Class 3 (23dBm \pm 2dB) for LTE TDD

UMTS/DC-HSPA+:

- 850/900/2100 MHz
- DC-HSPA+ mode: Max 42Mbps (DL) Max 5.76Mbps (UL)
- UMTS mode: 384 kbps DL, 384 kbps UL
- TD-SCDMA: Max 4.2Mbps (DL) Max 2.2Mbps (UL)
- Power Class 3 (24dBm +1/-3dB) for UMTS bands
- Class 3 (24dBm+1/-3dB) for TD-SCDMA

GSM/GPRS/EDGE:

- 900/1800 Mhz
- GPRS/EDGE Multi-slot Class 12
- Power Class E2 (27dBm \pm 3dB) for EDGE 850/900
- Power Class E2 (26dBm +3/-4dB) for EDGE 1800/1900
- Power Class 4 (33dBm \pm 2dB) for GSM 850/900
- Power Class 1 (30dBm \pm 2dB) for GSM 1800/1900

ETHERNET:

- IEEE 802.3, IEEE 802.3u standards
- 1 x LAN 10/100Mbps Ethernet port
- 1 x WAN 10/100Mbps Ethernet port
- Supports auto MDI/MDIX

WIFI:

- IEEE 802.11b/g/n WiFi standards
- AP and STA modes
- 64/128-bit WEP, WPA, WPA2, WPA&WPA2 encryption methods
- 2.401-2.495GHz WiFi frequency range
- 20dBm max WiFi TX power
- SSID stealth mode and access control based on MAC address

Caricatore

- Voltaggio ingresso: 220-240 VAC, 50-60 Hz
- Voltaggio carica: 14,4 /14.7 V, DC
- Corrente carica: 0,8 / 3.8 A (46W)
- 7 fasi
- 3 programmi
- Temperatura di lavoro: -20°C / +50°C
- Ciclo di carica automatico
- Peso: 0.5 KG

