

## Caratteristiche tecniche

### Kit di videosorveglianza e-Killer Snake



- Dimensioni 410 x 350 x H 170 mm
- Registrazione su SD 128 GB
- Router Wi-Fi 4G
- Alimentazione: n.2 batterie 12V 18A (incluse)
- Autonomia 48 ore
- Doppio fusibile di protezione
- Pulsante per spegnimento Wi-Fi
- Caricatore 3.8A intelligente
- 1/2,5" 4Megapixel progressive scan
- H.265&H.264 triple-stream encoding
- 25/30fps@4Mp(2560x1440)
- WDR(105dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, IR 150mt 850nm
- 4,7 mm ~ 94 mm motorized lens
- 2/1 Alarm in/out, 1/1 audio in/out
- IP67, PoE
- Funzioni analisi video

### Connettività 4G/Wi-Fi/Ethernet

- Slot sim push
- Pulsante attivazione/disattivazione rete wi-fi

### Reti

#### LTE:

- LTE FDD: B1/B3/B5/B7/B8/B20
- LTE TDD: B38/B40/B41
- LTE CAT4 up to 70 Mbps DL
- Class 3 (23dBm±2dB) for LTE FDD
- Class 3 (23dBm±2dB) for LTE TDD

#### UMTS/DC-HSPA+:

- 850/900/2100 MHz
- DC-HSPA+ mode: Max 42Mbps (DL) Max 5.76Mbps (UL)
- UMTS mode: 384 kbps DL, 384 kbps UL
- TD-SCDMA: Max 4.2Mbps (DL) Max 2.2Mbps (UL)
- Power Class 3 (24dBm +1/-3dB) for UMTS bands
- Class 3 (24dBm+1/-3dB) for TD-SCDMA

**GSM/GPRS/EDGE:**

- 900/1800 Mhz
- GPRS/EDGE Multi-slot Class 12
- Power Class E2 (27dBm  $\pm$ 3dB) for EDGE 850/900
- Power Class E2 (26dBm +3/-4dB) for EDGE 1800/1900
- Power Class 4 (33dBm  $\pm$ 2dB) for GSM 850/900
- Power Class 1 (30dBm  $\pm$ 2dB) for GSM 1800/1900

**ETHERNET:**

- IEEE 802.3, IEEE 802.3u standards
- 1 x LAN 10/100Mbps Ethernet port
- 1 x WAN 10/100Mbps Ethernet port
- Supports auto MDI/MDIX

**WIFI:**

- IEEE 802.11b/g/n WiFi standards
- AP and STA modes
- 64/128-bit WEP, WPA, WPA2, WPA&WPA2
- 2.401-2.495GHz WiFi frequency range
- 20dBm max WiFi TX power
- SSID stealth mode and access control based on MAC address